

# PNS1250

Portable Diesel Oil-Free Screw Compressor: OFH1250



## General Information PNS1250

Dimensions LxWxH (mm)	5240 x 2210 x 2350
Mass (Wet - Ready to operate) (kg)	8641
Fuel Tank Capacity (l)	900
Discharge Outlet	80mm Evertite 2" Male Spud with Gasket
Sound Pressure Level (7m) dB (A)	76

## Engine Cummins QSX15 CAT C18

Power (kW)	395	429
Fuel Consumption (100% load) (l/h)	84	95

## Performance Capacity (Free Air Delivery)

Working Pressure	cfm	m <sup>3</sup> /min	l/s
Pressure between 6 and 20,4 bar(g)	1250	35	575
Pressure between 20,5 and 24 bar(g)	1200	33	566

## Other features

9 Kg Fire Extinguisher	Emergency Stop Switch	Spillage Free Frame
Hot Air Outlet	Fork Lift Slots & Lifting Eye	Integrated Aftercooler + Water Separator
Spark Arrestor + Inlet Shutdown Valve(Amot)	Ansul Automated Fire Suppression System	Strobe light Indicating Unit is operational
Class Zero Certified (Oil-Free Acc to ISI8573-1)	SANS Government Approved Safety Relieve Valve and Vessel Certificate	Satellite Monitoring System



AIR



POWER



TEMPERATURE



FLOW

[www.randair.com](http://www.randair.com)

Rand-Air South Africa (Pty) Ltd.

Subject to change without prior notice. Information is for guidance only. Please contact your nearest Rental office for detailed application advice.