

PTE1500

Portable Electric Oil-Free Screw Compressor: PTE1500



General Information

Dimensions LxWxH (mm)	5440 x 2210 x 2350
Mass (Wet - Ready to operate) (kg)	6850
Discharge Outlet	80mm Evertite 3" Male Spud with Gasket
Sound Pressure Level (7m) dB (A)	98

Engine

Cummins QSX15

Power (kW)	300/400
Voltage (V)	400
Frequency (Hz)	50
Start Up Amps (A)	1200
Running Amps @ 7-10 bar (A)	500-560
Circuit Breaker (A)	630
Cabling	2 x 120mm

Performance

Capacity (Free Air Delivery)

Working Pressure	cfm	m ³ /min	l/s
Pressure up to 6,9 bar (g)	1613	45,7	792
Pressure up to 9,3 bar (g)	1522	43,1	718
Pressure up to 10,3 bar (g)	1320	37,4	623

Other features

9 Kg Fire Extinguisher	Emergency Stop Switch	Spillage Free Frame
Hot Air Outlet	Integrated Aftercooler + Water Separator	Fork Lift Slots & Lifting Eye
Strobe light Indicating Unit is operational	Class Zero Certified (Oil-Free Acc to ISI8573-1)	SANS Government Approved Safety Relieve Valve and Vessel Certificate



AIR



POWER



TEMPERATURE



FLOW

www.randair.com

Rand-Air South Africa (Pty) Ltd.

Subject to change without prior notice. Information is for guidance only. Please contact your nearest Rental office for detailed application advice.