

PTE900 VSD+

Portable Electric Oil-Free Screw
Compressor: PTE900 VSD+



General Information

Dimensions LxWxH (mm) (Trailer Mounted)	2800 x 2000 x 2400
Mass (Wet - Ready to operate) (kg)	4400
Discharge Outlet	80mm Evertite 3" Male Spud with Gasket
Sound Pressure Level (7m) dB (A)	99
Operating Temperature (°C)	-20 / 45
Cold Outlet Temperature (A+ °C)	10
Cold Outlet (Valve)	DN50
Hot Outlet (DIN)	DN50 PN16

Engine

Power (kW)	200
Voltage (V)	380-480
Frequency (Hz)	50/60
Adjustable Max Amps (A)	200—600
Cabling	120mm

Performance

Capacity (Free Air Delivery)

Working Pressure	cfm	m ³ /min	Total Package Power (kW)
Pressure up to 4 bar (g)	1000	1700	175
Pressure up to 7 bar (g)	900	1530	180
Pressure up to 10 bar (g)	800	1350	200

Other features

9 Kg Fire Extinguisher	Emergency Stop Switch	Spillage Free Frame
Hot Air Outlet	Integrated Aftercooler + Water Separator	Fork Lift Slots & Lifting Eye
Strobe light Indicating Unit is operational	Class Zero Certified (Oil-Free Acc to ISI8573-1)	SANS Government Approved Safety Relieve Valve and Vessel Certificate



AIR



POWER



TEMPERATURE



FLOW

www.randair.com

Rand-Air South Africa (Pty) Ltd.

Subject to change without prior notice. Information is for guidance only.
Please contact your nearest Rental office for detailed application advice.