

PTS916/PTS1600

Portable Diesel Oil-Free Screw
Compressor: OF1500



General Information

Dimensions LxWxH (mm)	5240 x 2210 x 2350
Mass (Wet - Ready to operate) (kg)	8560
Fuel Tank Capacity (l)	900
Discharge Outlet	80mm Evertite 2" Male Spud with Gasket
Sound Pressure Level (7m) dB (A)	76

Engine

Cummins QSX15

CAT C18

Power (kW)	395	429
Fuel Consumption (100% load) (l/h)	84	95

Performance

Capacity (Free Air Delivery)

Working Pressure	cfm	m ³ /min	l/s
Pressure up to 6,9 bar (g)	1613	45,7	792
Pressure up to 9,3 bar (g)	1522	43,1	718
Pressure up to 10,3 bar (g)	1320	37,4	623

Other features

9 Kg Fire Extinguisher	Emergency Stop Switch	Spillage Free Frame
Hot Air Outlet	Fork Lift Slots & Lifting Eye	Integrated Aftercooler + Water Separator
Spark Arrestor + Inlet Shutdown Valve (Amot)	Ansul Automated Fire Suppression System	Strobe light Indicating Unit is operational
Class Zero Certified (Oil-Free Acc to ISI8573-1)	SANS Government Approved Safety Relieve Valve and Vessel Certificate	Satellite Monitoring System



AIR



POWER



TEMPERATURE



FLOW

www.randair.com

Rand-Air South Africa (Pty) Ltd.

Subject to change without prior notice. Information is for guidance only.
Please contact your nearest Rental office for detailed application advice.