ZT132 Electric Driven Oil-Free Screw Compressor: ZT132





General Information			ZT132	
Dimensions LxWxH (mm)	3400 x 1650 x 2150			
Mass (Wet - Ready to operate) (kg)	3850			
Discharge Outlet	80mm Evertite 2" Male Spud with Gasket			
Sound Pressure Level (7m) dB (A)	79			
Engine		W	/EG 400/4355M/L	
Main Electric Motor Power (kW)			132	
Voltage (V)			400	
Frequency (Hz)			50	
Start Up Amps (A)	723 A			
Full Load Running Amps @ 7-10 bar (A)	241 A			
Supply Circuit Breaker (A)	350 A			
Electric Supply Cabling	70mm			
Performance	Capacity (Free Air Delivery)			
Working Pressure	cfm	m³/min	l/s	
Pressure up to 7,5 bar(g)	758	21,5	358	
Other features				
Emergency Stop Switch	Reliable Motor & Drive Train	n	Fork Lift Slots	
Robust & Silent	Water Separator Elektro		Elektronikon Touch Display	
Fitted with Phase Protection Relay	Integrated Aftercooler (Cert	ain Fleet Models only)	SANS Government Approved Safety Relieve Valve and Vessel Certificate	







www.randair.com

Rand-Air South Africa (Pty) Ltd.

Subject to change without prior notice. Information is for guidance only. Please contact your nearest Rental office for detailed application advice.

ZT90 VARIOUS

Electric Driven Oil-Free Screw Compressor: ZT90 Various





General Information	ZT90)	ZT90 FF	ZT90VSD FF	
Dimensions LxWxH (mm)	3400 x 1650	x 2150	4085 x 1650 x 2150	4085x 1650 x 2150	
Mass (Wet - Ready to operate) (kg)	3850		4250	4250	
Discharge Outlet	50mm Evertite 2" Male Spud 50mm Evertite 2" Male S with Gasket with Gasket		50mm Evertite 2" Male Spud with Gasket	50mm Evertite 2" Male Spud with Gasket	
Sound Pressure Level (7m) dB (A)	79		79	79	
Engine	ZT90		ZT90 FF	ZT90VSD FF	
Main Electric Motor Power (kW)	90		90	90	
Voltage (V)	400		400	400	
Frequency (Hz)	50		50	50	
Start Up Amps (A)	400 A		400 A	400 A	
Full Load Running Amps @ 7-10 bar (A)	300 A		300 A	300 A	
Supply Circuit Breaker (A)	350 A		350 A	350 A	
Electric Supply Cabling	35mm	ı	35mm	35mm	
Performance			Capacity (Free Air Del	ivery)	
Working	Pressure	cfm	m³/min	l/s	
ZT90 & ZT90 FF Pressure up t	o 7,5 bar(g)	500	14,2	236	
ZT90 VSD & ZT90 VSD FF Pressure up t	o 8,6 bar(g)	212—534	6.0—15,1	100—252	
Other features					
Emergency Stop Switch	Reliable Motor & Drive Train		Fork Lift Slots		
Robust & Silent	Water Separator		Elektronikon Touch Display		

Fitted with Phase Protection Relay

FLOW

www.randair.com

Integrated Aftercooler (Certain Fleet Models only)

Rand-Air South Africa (Pty) Ltd.

Subject to change without prior notice. Information is for guidance only. Please contact your nearest Rental office for detailed application advice

SANS Government Approved Safety Relieve

Valve and Vessel Certificate

ZT22 Electric Driven Oil-Free Screw Compressor: Various ZT22





General Information	ZT22	ZT22 FF		ZT22 VSD	
Dimensions LxWxH (mm)	1760 x 1026 x 1621	1760 x 1026 x 1621		2195 x 1028 x 1621	
Mass (Wet - Ready to operate) (kg)	1001	1286		1120	
Discharge Outlet	50mm Evertite 2" Male Spud with Gasket	50mm Evertite 2'' Male Spud with Gasket		50mm Evertite 2" Male Spud with Gasket	
Sound Pressure Level (7m) dB (A)	72	72		72	
Engine	ZT22	ZT22 FI	F	ZT22 VSD	
Main Electric Motor Power (kW)	22	22		22	
Voltage (V)	400	400		400	
Frequency (Hz)	50	50		50	
Start Up Amps (A)	160 A	160 A		160 A	
Full Load Running Amps @ 7-10 bar (A)	60 A	60 A		60 A	
Supply Circuit Breaker (A)	100 A	100 A		100 A	
Electric Supply Cabling	16mm	16mm		16mm	
Performance	Capacity (Free Air Delivery)				
Working Pressure	cfm	m³/min		l/s	
Pressure up to 7,25 bar(g)	126	3,57		59,5	
Other features					
Emergency Stop Switch	Reliable Motor & Drive Train		Fork Lift Slots		
Robust & Silent	Water Separator		Elektronikon Touch Display		
Fitted with Phase Protection Relay	Integrated Aftercooler (Certain Fleet Models only)		SANS Government Approved Safety Relieve Valve and Vessel Certificate		





POWER



www.randair.com

Rand-Air South Africa (Pty) Ltd.

Subject to change without prior notice. Information is for guidance only. Please contact your nearest Rental office for detailed application advice.