



QAS80

Atlas Copco QAS80 Silenced Generator; G080



General information

Dimension LxWxH (mm) - (trailer mounted)	5000x1630x2100	
Mass (wet) (kg) - (trailer mounted)	2250	
Dimensions LxWxH (mm) - (removed from trailer)	2850x1100x1635	
Mass (wet) (kg) - (removed from trailer)	1994	
Fuel tank capacity (l)	230	
Frequency (Hz)	50	60
Sound power level LWA dB (A)	67	67
Prime Rated Power (KVA/KW)	80/64	93/74.4
Voltage (V)	400	480
Nom. Current (A)	115.5	111.9
Fuel Consumption at 100% load (l/hr)	19.8	23.8
Fuel Consumption at 75% load (l/hr)	14.9	19
Min/Max Ambient (°C)	-18/50	-18/50

Main features

Strobe light (Indicating Unit is operational)	Bus Bar	9 Kg Fire Extinguisher
Spillage Free	Recommended Cable - 1 x 50mm - 5 core	4-Pole Battery Isolator Switch
External fuel tank connection	Trailer Mounted	Emergency Stop Switch
Paralleling	Remote + Auto start	AMF

Accessories

Cables	Transformers
Distribution boards	External fuel tank

* Latest units fitted with DB board:

2 x 63-Amp 5-pin C-Form plugs; 2 x 32-Amp 5-pin C-Form plugs

4 x 16-Amp 3-pin C-Form plugs; 4 x 16-Amp 220 volt plugs