



# XA(S)186

Portable Diesel Oil-Injected Screw Compressor: D400



## General Information

Dimensions LxWxH (mm)	4356 x 1716 x 1661
Mass (Wet—Ready to operate) (kg)	1825
Fuel tank capacity (l)	180
Discharge Outlet	1 x 50mm Evertite 2" Male Spud with Gasket 2 x 3/4" Chicago Claw Coupling with Gaskets
Sound pressure level (7m) dB (A)	73

## Engine DUETZ TCD2012 L04

Power (kW)	83
Fuel Consumption (100% load) (l/h)	18

## Performance Without Aftercooler

Max Working Pressure		Free Air Delivery		
bar(g)	psi	cfm	m <sup>3</sup> /min	lts/ sec
7	102	395	11.1	185

## Performance With Aftercooler

Max Working Pressure		Free Air Delivery		
bar(g)	psi	cfm	m <sup>3</sup> /min	lts/ sec
7	102	386	10.9	182

## Other features

Strobe light (Indicating Unit is operational)	Emergency Stop Switch	Lifting Eye
9 Kg Fire Extinguisher	Integrated Aftercooler + Water Separator (Certain Fleet Units)	Spark Arrestor + Inlet Shutdown Valve (Amot) - (Certain Fleet Units)
4-Pole Battery Isolator Switch & Enclosed Battery Box	SANS Government Approved Safety Relieve Valve and Vessel Certificate	Road Worthy with LED Taillights