



XAMS527

Portable Diesel Oil-Injected Screw Compressor: D1000



General Information

Dimensions LxWxH (mm)	4900 x 2140 x 2480
Mass (Wet—Ready to operate) (kg)	6800
Fuel tank capacity (l)	820
Discharge Outlet	50mm Evertite 2" Male Spud with Gasket
Sound pressure level (7m) dB (A)	72

Engine CAT C09

Power (kW)	224
Fuel Consumption (100% load) (l/h)	52

Performance Without Aftercooler

Max Working Pressure		Free Air Delivery		
bar(g)	psi	cfm	m ³ /min	lts/ sec
8.6	125	1102	31.2	520

Performance With Aftercooler

Max Working Pressure		Free Air Delivery		
bar(g)	psi	cfm	m ³ /min	lts/ sec
8.6	125	1001	28.3	471

Other features

Spillage free frame	Emergency Stop Switch	Forklift Slots + Lifting Eye
9 Kg Fire Extinguisher	Integrated Aftercooler + Water Separator (Certain Fleet Units)	Spark Arrestor + Inlet Shutdown Valve (Amot) - (Certain Fleet Units)
Satellite Monitoring System	SANS Government Approved Safety Relieve Valve and Vessel Certificate	Strobe light (Indicating Unit is operational)