



# XATS377

Portable Diesel Oil-Injected Screw Compressor: D770



## General Information

Dimensions LxWxH (mm)	5074 x 1988 x 2094
Mass (Wet—Ready to operate) (kg)	3450
Fuel tank capacity (l)	375
Discharge Outlet	1 x 50mm Evertite 2" Male Spud with Gasket 2 x 3/4" Chicago Claw Coupling with Gaskets
Sound pressure level (7m) dB (A)	72

## Engine CAT C7

Power (kW)	186
Fuel Consumption (100% load) (l/h)	41

## Performance Without Aftercooler

Max Working Pressure		Free Air Delivery		
bar(g)	psi	cfm	m <sup>3</sup> /min	lts/ sec
10.3	149	782	22.1	368

## Performance With Aftercooler

Max Working Pressure		Free Air Delivery		
bar(g)	psi	cfm	m <sup>3</sup> /min	lts/ sec
10.3	149	760	21.5	358

## Other features

Strobe light (Indicating Unit is operational)	Emergency Stop Switch	Lifting Eye
9 Kg Fire Extinguisher	Integrated Aftercooler + Water Separator (Certain Fleet Units)	Spark Arrestor + Inlet Shutdown Valve (Amot) - (Certain Fleet Units)
SANS Government Approved Safety Relieve Valve and Vessel Certificate		