



# XRHS366

Portable Diesel Highpressure Oil-Injected Screw Compressor: H752



## General Information

Dimensions LxWxH (mm)	4980 x 2100 x 2460
Mass (Wet—Ready to operate) (kg)	6520
Fuel tank capacity (l)	538
Discharge Outlet	50mm Evertite 2" Male Spud with Gasket
Sound pressure level (7m) dB (A)	72

Engine	CAT C9		
--------	--------	--	--

Power (kW)	224	
Fuel Consumption (100% load) (l/h)	45	

## Performance Without Aftercooler

Max Working Pressure		Free Air Delivery		
bar(g)	psi	cfm	m <sup>3</sup> /min	lts/ sec
20	290	773	21.8	365

## Performance With Aftercooler

Max Working Pressure		Free Air Delivery		
bar(g)	psi	cfm	m <sup>3</sup> /min	lts/ sec
20	290	765	21.6	360

## Other features

Spillage free frame	Emergency Stop Switch	Forklift Slots + Lifting Eye
9 Kg Fire Extinguisher	Integrated Aftercooler + Water Separator (Certain Fleet Units)	Spark Arrestor + Inlet Shutdown Valve (Amot) - (Certain Fleet Units)
Satellite Monitoring System	SANS Government Approved Safety Relieve Valve and Vessel Certificate	Strobe light (Indicating Unit is operational)