



XRVS476

Portable Diesel Highpressure Oil-Injected Screw Compressor: H952



General Information

Dimensions LxWxH (mm)	5640 x 2100 x 2460
Mass (Wet—Ready to operate) (kg)	6843
Fuel tank capacity (l)	796
Discharge Outlet	50mm Evertite 2" Male Spud with Gasket
Sound pressure level (7m) dB (A)	72

Engine CAT C13

Power (kW)	317
Fuel Consumption (100% load) (l/h)	63

Performance Without Aftercooler

Max Working Pressure		Free Air Delivery		
bar(g)	psi	cfm	m ³ /min	lts/ sec
25	363	975	27.6	459

Performance With Aftercooler

Max Working Pressure		Free Air Delivery		
bar(g)	psi	cfm	m ³ /min	lts/ sec
25	363	953	26.9	449

Other features

Spillage free frame	Emergency Stop Switch	Forklift Slots + Lifting Eye
9 Kg Fire Extinguisher	Integrated Aftercooler + Water Separator (Certain Fleet Units)	Spark Arrestor + Inlet Shutdown Valve (Amot) - (Certain Fleet Units)
Satellite Monitoring System	SANS Government Approved Safety Relieve Valve and Vessel Certificate	Strobe light (Indicating Unit is operational)